



PE-X Shrink Sleeve for Joint Casing



All dimensions are in mm

Sleeve cut length

ØD	L
90-200 mm	M* + 75 mm
225-500 mm	M* + 100 mm
≥ 560 mm	M* + 125 mm



M*: Circumferential length of Joint Casing in the sealing zone (after application for PE and PE-X joint casing).

Closure Patch width

Recommended application	100 mm
Acceptable application	150 mm
Possible application	200 mm

1. In combination with SHRINKABLE CASING (no gap)

Jacket Pipe Ø	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	670	710					
RJS-E/A																								
width 155																								
width 230																								
Jacket Pipe Ø	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	670	710					
RJS-E/B																								
width 155																								
width 230																								
Jacket Pipe Ø					160	180	200	225	250	280	315	355	400	450	500	560	630	670	710	800	900	1000	1200	
RJS-E/C																								
width 300																								

2. In combination with NON SHRINKABLE CASING (gap)

Jacket Pipe Ø	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	670	710	800	900	1000	1200	
RJS-E/B																								
width 155																								
width 230																								
RJS-E/C																								
width 300																								

Note: gap = distance in between top of PE jacket pipe and, inside of oversized casing when fully lifted. Maximum gap is 2,5 times oversized casing thickness. Casing must be bevelled.

AT-RJS-E-REV2-MART11 - LEXPS-0109