

<i>Max Casing diameter before shrinkage</i> mm	<i>Insulated Pipe diameter(s)</i> mm	<i>TPSM-PE product size</i>	<i>Product width xxx</i> mm	<i>Min supplied diameter TPSM-PE</i> mm	<i>Max recovered diameter TPSM-PE</i> mm
80	65	TPSM-85/60-XXXPE65(C150)	150	85	60
90	65 - 75	TPSM-95/65-XXXPE65/75(C125)	150	95	65
105	90	TPSM-115/80-XXXPE90(C90)	150 or 225	115	80
125	90 - 110	TPSM-130/90-XXXPE90/110(C90)	150 or 225	130	90
145	110 - 125	TPSM-155/100-XXXPE110/125(C90)	150 or 225	155	100
160	125 - 140	TPSM-170/110-XXXPE125/140(C90)	150 or 225	170	110
180	140 - 160	TPSM-190/125-XXXPE140/160(C90)	150 or 225	190	125
200	160 - 180	TPSM-210/135-XXXPE160/180(C60)	150 or 225	210	135
220	180 - 200	TPSM-225/145-XXXPE180/200(C60)	150 or 225	225	145
245	200 - 225	TPSM-260/165-XXXPE200/225(C60)	150 or 225	260	165
265	225 - 250	TPSM-290/185-XXXPE225/250(C40)	150 or 225	290	185
300	250 - 280	TPSM-330/210-XXXPE250/280(C44)	150 or 225	330	210
335	280 - 315	TPSM-370/235-XXXPE280/315(C44)	150 or 225	370	235
370	315 - 355	TPSM-395/250-XXXPE315/355(C30)	150 or 225	395	250
420	355 - 400	TPSM-450/285-XXXPE355/400(C30)	225	450	285
470	400 - 450	TPSM-505/315-XXXPE400/450(C20)	225	505	315
525	450 - 500	TPSM-555/350-XXXPE450/500(C20)	225	555	350
585	500 - 560	TPSM-625/385-XXXPE500/560(C14)	225	625	385
650	560 - 630 - 710	TPSM-775/480-XXXPE560/710(C10)	225	775	480
735	560 - 630 - 710	TPSM-775/480-XXXPE560/710(C10)	225	775	480
825	710 - 800	TPSM-865/525-XXXPE710/800(C10)	225	865	525