

- Characteristics:** Adhesive tape on rolls with release paper.
- Applications:** Used in combinations with CCS-DHEC and DHEC. Can be sold separately in case leak detection wires have to be brought out when installing CCS-DHEC or DHEC.  
Included in groupment packaging of IPEC. Double wrap of sealing strip is applied on the pipe before shrinking of IPEC.  
The adhesive tape can also be used on top of a weld bead of a girth weld, underneath a shrinksleeve to fill up and smoothen rough irregularities caused by welding 2 pipes together.
- Product description:** S1113-XXXxYYYxZZZ  
XXX = Width in mm  
YYY = Thickness in mm  
ZZZ = Length in mm
- Material properties:** Typical Softening point : 150°C  
Typical Shear strength @ 23°C : 30 N/cm<sup>2</sup> @ 50 mm/min  
Typical Peel strength @ 23°C : 30 N/cm @ 50 mm/min
- Dimensions:** Width: 30 mm, 40 mm, 50 mm  
Thickness: 1 mm  
Length per roll: 30000 mm
- Product printing & Labelling:** No printing.  
The box in which S1113 is packed, is bearing a label mentioning: Covalence Description, Part Number, Lotnbr, Quantity, Spec. Code
- Hot climates:** In hot climates (>30°C) it is recommended to use the S1113 strips with a plastic release liner. Ordering description: S1113-40X1X30000-PL(C4)
- Ordering Info:** S1113 rolls are packed in a box

S1113-	Quantity per box
30x1x30000(C5)	5
40x1x30000(C4)	4
50x1x30000(C3)	3