

POLYKEN[®] 1039

Product Information

Product description: Polyken[®] liquid adhesive systems are recommended for use with only Polyken[®] coating systems. The liquid adhesive systems consist of elastomers blended with polymeric resins dissolved in an organic solvent system. They can be used for machine or hand applications and provide excellent adhesion to the pipe substrate and cathodic disbondment resistance.

Polyken[®] 1039

This is a zero VOC liquid adhesive system that complies with the federal and state clean air requirements. The liquid adhesive is designed for machine or hand application in environmentally sensitive areas. Used in conjunction with the recommended Polyken[®] coating systems, the 1039 will provide the same long-term performance as the other Polyken[®] liquid adhesive systems.

Note:

- Properly stored, all Polyken[®] liquid coating systems have a shelf life of 3 years. Please request an application specification and storage guideline from Seal For Life.
- Store away from heat and use away from fire, flames, sparks, lighted cigarettes, etc. Read all label instructions prior to use.

Product selection guide

1039	
Solvent	Parachloro-benzotrifluoride
Base	Rubber/Resins
Solids %	20
Viscosity	Thin Syrup
Flash point	42.8°C (109°F)
Shelf life	3 Years
VOC content	0 (zero)
Weight	10.30 lb/gal 1.2 kg/l
Color	Black
Maximum operating temperature	185°F (85°C)

Ordering information

Polyken[®] Liquid Adhesives are available in different container quantities

Quantity	Ordering description
55 Gal or 208.2L	1039 LIQ ADH 55 GAL-208.2L
1 Gal or 3.8 L	1039 LIQ ADH 1 GAL-3.8L
1 QT or 0.95 L	1039 LIQ ADHES 1 QT (4QT/BOX)

For other ordering options please contact your Seal For Life representative.

Information

Documentation	Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our offices, from our local distributor or by sending an email to info@sealforlife.com
Certified staff	Application of the described coating system should be carried out by certified personnel.



PART OF THE BERRY PLASTICS ENGINEERED MATERIALS DIVISION

Anodex[®] – Stopaq[®] – Polyken[®] – Covalence[®] – Powercrete[®]

SEAL FOR LIFE TECHNOLOGY CENTRE

Gasselterstraat 20, 9503 JB Stadskanaal
the Netherlands
www.sealforlife.com

Seal For Life Industries LLC
Houston, TX, USA
Tel: +1 713 676 0085
US Toll Free: +1 888 676 7202
Fax: +1 713 676 0086
houston@sealforlife.com

Seal For Life Industries BV
Stadskanaal, the Netherlands
Tel: +31 599 696 170
Fax: +31 599 696 177
info@sealforlife.com

Seal For Life Industries
Tijuana, Mexico
Tel USA: +1 858 633 9797
Fax USA: +1 858 633 9740
Tel Mexico: +52 664 647 4397
Fax Mexico: +52 664 607 9105
mexico@sealforlife.com

Seal For Life Industries BVBA
Westerlo, Belgium
Tel: +32 14 722 500
Fax: +32 14 722 570
belgium@sealforlife.com

Seal For Life Private Ltd.
Baroda, India
Tel: +91 2667 264 721
Fax: +91 2667 264 724
india@sealforlife.com

DISCLAIMER: Berry Plastics warrants that the product(s) represented within conform(s) to its/their chemical and physical description and is appropriate for the use as stated on the respective technical data sheet when used in compliance with Berry Plastics written instructions. Since many installation factors are beyond the control of Berry Plastics, the user is obligated to determine the suitability of the products for the intended use and assume all risks and liabilities in connection herewith. Berry Plastics liability is stated in the standard terms and conditions of sale. Berry Plastics makes no other warranty either expressed or implied. All information contained in the respective technical data sheet(s) should be used as a guide and is subject to change without notice. This document supersedes all previous revisions. Please see revision date below. Polyken[®] is a registered trademark of Berry Plastics Corporation.